


## Clear Fire Resistant Safety Glass Ceramic

### CLASSIFICATION



### PRODUCT FEATURES

- Tempered or Laminated Safety Glass
- Glass Ceramic
- Intumescent Interlayer



### TECHNICAL SPECIFICATIONS

Fire Resistive	20 – 180 Minute
Testing / Compliant	Listed and labeled with Underwriters Laboratories Inc. File #R14515 Tested in accordance with UL 9, UL 10C, NFPA 80, NFPA 251, NFPA 252 NFPA 257
Impact Safety Rating	CPSC 16CFR PART 1201 (CATEGORIES I & II)
Nominal Thickness	3/4" (18 mm) or 7/8" (22mm) <sup>1</sup>
Thickness Tolerance	0.719" to 0.781"
U value (BTU/hr*sqft/°F)	0.88
STC Rating	37
Weight (lbs/sq.ft.)	6
Visible Light Transmission	~ 80%

### AUTHORIZED DIMENSIONS

Rating	Application	Max Exposed Area of Glass (Sq In.)	Max Width of Exposed Glass	Max Height of Exposed Glass	Min Depth of Groove	Groove Width	Building Code Marking <sup>2</sup>
3/4 hr	Door-Non Temp Rise	2736	46-1/2"	76"	5/8"	29/32"	D-H-NT-45
3/4 hr	Window, Transom, Sidelight	2736	60-1/2"	76"	5/8"	29/32"	D-H-NT-45, OH-45
1 hr	Door-Non Temp Rise	2736	46-1/2"	76"	5/8"	29/32"	D-H-NT-60
1 hr	Door-Temp Rise	100	10"	33"	5/8"	29/32"	D-H-NT-60
1 hr	Window, Transom, Sidelight	2736	46-1/2"	76"	5/8"	29/32"	D-H-NT-60, OH-60
1-1/2 hr	Door-Non Temp Rise	2736	46-1/2"	76"	5/8"	29/32"	D-H-NT-90
1-1/2 hr	Door-Temp Rise	100	10"	33"	5/8"	29/32"	D-H-NT-90
1-1/2 hr	Window, Transom, Sidelight	2736	60-1/2"	76"	5/8"	29/32"	D-H-NT-90, OH-90
3 hr	Door-Temp Rise	100	10"	33"	5/8"	29/32"	D-H-NT-180

<sup>1</sup> For sizes under 8" width or height

<sup>2</sup> See Reference Page